



GOOD MANUFACTURING PRACTICES  
CERTIFICATE NUMBER GSCGMP-1-121  
Based on: NOM-251-SSA1-2009

## FIBERGLASS EXTENSION POLES

1" diameter pole made of fiberglass, with a 3/4" threaded tip and a length of 1.37 m (retracted) up to 2.40 m (extended). Compatible with any product with threaded perforation in our line. Available in 5 colors for color coding areas.

PIECE			PACK				PALLET			20 FT CONTAINER		48 FT CONTAINER		53 FT CONTAINER	
CODE	SIZE	Ø	APPROX. WEIGHT	MEASUREMENTS HEIGHT X WIDTH X LENGTH	CASE QTY.	WEIGHT	CASES	WEIGHT	PIECES	CASES	PIECES	CASES	PIECES	CASES	PIECES
193240	55.12 in	1.5 in	2.12 lb	5.51 x 7.48 x 57.87 in	12	25.44 lb	-	-	-	-	-	-	-	-	-

### GENERAL SPECIFICATIONS

SUNLIGHT RESISTANCE		ABRASION RESISTANCE		WATER ABSORPTION		STIFFNESS		ELASTIC RECOVERY	
HANDLE	GRIP	HANDLE	GRIP	HANDLE	GRIP	HANDLE	GRIP	HANDLE	GRIP
G	E	A	G	D	D	A	E	E	E

### CHEMICAL AND MOISTURE RESISTANCE

MOISTURE		DILUTED ACID		CONCENTRATED ACID		DILUTED ALKALI		ALCOHOL AND VEGETABLE OILS		PETROLEUM DISTILLATES	
HANDLE	GRIP	HANDLE	GRIP	HANDLE	GRIP	HANDLE	GRIP	HANDLE	GRIP	HANDLE	GRIP
E	E	E	E	E	E	E	E	E	E	A	E

\* Depending on the color of the handle the following letter could be added to the product's code:

CODE				
BLUE	GREEN	RED	WHITE	YELLOW
+FB	+FG	+FR	+FW	+FY

### SUGGESTED APPLICATION:

Ideal in electrical component installations, etc.

### CONTRAINdicATIONS:

Its use is not recommended in environments where there is direct contact with fire.

### SUPPLEMENTARY PRODUCTS:

All products with HACCP coding, especially brushes with PBT fibers.

