



GOOD MANUFACTURING PRACTICES
CERTIFICATE NUMBER GSCGMP-1-121
Based on: NOM-251-SSA1-2009

GARBAGE CAN WITH FRONT-FACING SLOTTED LID

60 liter garbage can with frontfacing slotted lid for paper, manufactured with polypropylene.

PIECE				PACK			PALLET			20 FT CONTAINER		48 FT CONTAINER		53 FT CONTAINER	
PIECE	CODE	MEASUREMENTS HEIGHT X WIDTH X LENGTH	APPROX. WEIGHT	MEASUREMENTS HEIGHT X WIDTH X LENGTH	CASE QTY.	WEIGHT	CASES	WEIGHT	PIECES	CAJAS/ ATADOS	PIEZAS	CAJAS/ ATADOS	PIEZAS	CAJAS/ ATADOS	PIEZAS
GARBAGE CAN WITH FRONT-FACING SLOTTED LID	TC060-03-GY	31.10 X 12.20 X 15.75 in	6.39 lb	34.45 X 13.19 X 18.11 in	3	28.66 lb	-	-	-	-	-	-	-	-	-

GENERAL SPECIFICATIONS

SUNLIGHT RESISTANCE		ABRASION RESISTANCE		WATER ABSORPTION		STIFFNESS		ELASTIC RECOVERY	
CAN	LID	CAN	LID	CAN	LID	CAN	LID	CAN	LID
G	G	A	E	D	D	A	E	E	D

THERMAL RESISTANCE*				CHEMICAL AND MOISTURE RESISTANCE											
DISTORTION		SOFTENING		MOISTURE		DILUTED ACID		CONCENTRATED ACID		DILUTED ALKALI		ALCOHOL AND VEGETABLE OILS		PETROLEUM DISTILLATES	
CAN	LID	CAN	LID	CAN	LID	CAN	LID	CAN	LID	CAN	LID	CAN	LID	CAN	LID
176 °F	176 °F	266 °F	266 °F	E	A	E	A	E	D	E	A	E	G	G	G

SUGGESTED APPLICATION:

Collection of paper and cardboard.

CONTRAINdicATIONS:

DNA

SUPPLEMENTARY PRODUCTS:

DNA



CFS BRANDS