



GOOD MANUFACTURING PRACTICES  
CERTIFICATE NUMBER GSCGMP-1-121  
Based on: NOM-251-SSA1-2009

HANDLE ADAPTER

Plastic adapter, which allows the use of Pulex® and Moerman® brand floor squeegees (those that do not have a threaded connection) making them compatible with all our threaded tip poles. Recommended for Pulex® and Moerman® brand industrial squeegees. (Cane and squeegee sold separately.).

| PIECE |                            |                   | PACK                                    |           |         | PALLET |            |        | 20 FT CONTAINER |        | 48 FT CONTAINER |         | 53 FT CONTAINER |         |
|-------|----------------------------|-------------------|---|-----------|---------|--------|------------|--------|-----------------|--------|-----------------|---------|-----------------|---------|
| CODE  | MEASUREMENTS<br>LENGTH X Ø | APPROX.<br>WEIGHT | MEASUREMENTS<br>HEIGHT X WIDTH X LENGTH | CASE QTY. | WEIGHT  | CASES  | WEIGHT     | PIECES | CASES           | PIECES | CASES           | PIECES  | CASES           | PIECES  |
| 1999  | 2.5 x 1 in                 | 0.022 lb          | 2.75 x 5.12 x 7.48 in                   | 12        | 0.57 lb | 4500   | 2612.48 lb | 54000  | 45000           | 540000 | 108000          | 1296000 | 117000          | 1404000 |

| GENERAL SPECIFICATIONS |  |                     |  |                  |  |           |  |
|------------------------|--|---------------------|--|------------------|--|-----------|--|
| SUNLIGHT RESISTANCE    |  | ABRASION RESISTANCE |  | WATER ABSORPTION |  | STIFFNESS |  |
| G                      |  | G                   |  | D                |  | G         |  |

| THERMAL RESISTANCE* |           | CHEMICAL AND MOISTURE RESISTANCE |              |                   |                |                               |                          |
|---------------------|-----------|----------------------------------|--------------|-------------------|----------------|-------------------------------|--------------------------|
| DISTORTION          | SOFTENING | MOISTURE                         | DILUTED ACID | CONCENTRATED ACID | DILUTED ALKALI | ALCOHOL AND<br>VEGETABLE OILS | PETROLEUM<br>DISTILLATES |
| 176 °F              | 266 °F    | E                                | E            | E                 | E              | E                             | G                        |

**SUGGESTED APPLICATION:**  
For the use of Pulex® cleaning implements with any of our threaded handles.

**CONTRAINDICATIONS:**  
DNA

**SUPPLEMENTARY PRODUCTS:**  
All the handles in our line.



(El jalador y el bastón se venden por separado)

(\* These temperature was determined at constant exposure to heat / (\*) Intermittent exposure does not affect it)

The information provided on this document is for illustrative purposes and may change without notice.