

SHEET METAL HANDLES



GOOD MANUFACTURING PRACTICES
CERTIFICATE NUMBER GSCGMP-1-121
Based on: NOM-251-SSA1-2009

34 caliber sheet metal baton with 3/4" threaded plastic tip, covered with plastic film. This cane is the most economical option in our line of threaded canes. Available in 48" length and 54" m length. Sheet gauge used is much higher than that used by our competitors.

PIECE				PACK			PALLET			20 FT CONTAINER		48 FT CONTAINER		53 FT CONTAINER	
CODE	SIZE	Ø	APPROX. WEIGHT	MEASUREMENTS HEIGHT X WIDTH X LENGTH	CASE QTY.	WEIGHT	CASES	WEIGHT	PIECES	CASES	PIECES	CASES	PIECES	CASES	PIECES
1901-M	48 in	0.87 in	0.53 lb	48 X 5 X 5 in	24	13 lb	216	2738 lb	5184	2160	51840	5184	124416	5616	134784
1905-M	54 in	0.87 in	0.57 lb	54 X 5 X 5 in	24	14 lb	80	1127 lb	1920	800	19200	1920	46080	2080	49920

GENERAL SPECIFICATIONS									
SUNLIGHT RESISTANCE		ABRASION RESISTANCE		WATER ABSORPTION		STIFFNESS		ELASTIC RECOVERY	
GRIP	HANDLE	GRIP	HANDLE	GRIP	HANDLE	GRIP	HANDLE	GRIP	HANDLE
G	E	G	A	D	D	G	G	D	D

CHEMICAL AND MOISTURE RESISTANCE											
MOISTURE		DILUTED ACID		CONCENTRATED ACID		DILUTED ALKALI		ALCOHOL AND VEGETABLE OILS		PETROLEUM DISTILLATES	
GRIP	HANDLE	GRIP	HANDLE	GRIP	HANDLE	GRIP	HANDLE	GRIP	HANDLE	GRIP	HANDLE
E	A	E	A	E	D	E	D	E	G	A	G

SUGGESTED APPLICATION:

Handling cleaning tools.

CONTRAINDICATIONS:

Its use with diluted acids and alkalis is not recommended, nor its direct contact with food.

SUPPLEMENTARY PRODUCTS:

All the products with threaded handle holes.

