

## SOCKET FLOOR SQUEEGEE



**GOOD MANUFACTURING PRACTICES**  
 CERTIFICATE NUMBER GSCGMP-1-121  
 Based on: NOM-251-SSA1-2009

20" squeegee with high-impact polypropylene connector with interior threading (suitable for our threaded handles) and highgauge galvanized metal channel, appropriate for heavy-duty applications. This squeegee is part of our interchangeable handle system that allows for different tools to be used with the same handle, resulting in significant savings. In addition, when the rubber wears out, you keep the handle and only have to pay for the cost of replacing the squeegee.

PIECE			PACK			PALLET			20 FT CONTAINER		48 FT CONTAINER		53 FT CONTAINER	
CODE	MEASUREMENTS HEIGHT X WIDTH X LENGTH	APPROX. WEIGHT	MEASUREMENTS HEIGHT X WIDTH X LENGTH	CASE QTY.	WEIGHT	CASES	WEIGHT	PIECES	CASES	PIECES	CASES	PIECES	CASES	PIECES
7104-I	20 X 4.72 X 3 in	1.10 lb	7.1 X 7.7 X 20 in	12	14.33 lb	96	1408.75 lb	1152	960	11520	2304	27648	2496	29952

### GENERAL SPECIFICATIONS

SUNLIGHT RESISTANCE			ABRASION RESISTANCE			WATER ABSORPTION			STIFFNESS			ELASTIC RECOVERY		
HANDLE	CHANNEL	RUBBER	HANDLE	CHANNEL	RUBBER	HANDLE	CHANNEL	RUBBER	HANDLE	CHANNEL	RUBBER	HANDLE	CHANNEL	RUBBER
G	G	G	A	E	E	D	D	A	A	E	DNA	E	D	E

### RESISTENCIA A LA HUMEDAD Y AGENTES QUÍMICOS

HUMEDAD			ÁCIDOS DILUÍDOS			ÁCIDOS CONCENTRADOS			ALCALIS DILUÍDOS (SOSA)			ALCOHOL Y ACEITES VEGETALES			DESTILADOS DE PETRÓLEO		
HANDLE	CHANNEL	RUBBER	HANDLE	CHANNEL	RUBBER	HANDLE	CHANNEL	RUBBER	HANDLE	CHANNEL	RUBBER	HANDLE	CHANNEL	RUBBER	HANDLE	CHANNEL	RUBBER
E	A	E	E	A	G	E	D	A	E	A	E	E	G	E	G	G	D

#### SUGGESTED APPLICATION:

Designed for general floor cleaning.

#### CONTRAINDICATIONS:

Must not be exposed to the environment for long periods of time.

#### SUPPLEMENTARY PRODUCTS:

Recommended for use with 1901, 1901-M, 1904, 1905, 1905-M and 1901-M handles and telescopic poles..

