

GOOD MANUFACTURING PRACTICES CERTIFICATE NUMBER GSCGMP-1-121 Based on: NOM-251-SSA1-2009

(🗍 🗍 🖓 🖓 🖓 🕺 🖓 🖓 🖓 🖓



PIECE			РАСК			PALLET			20 FT CONTAINER		48 FT CONTAINER		53 FT CONTAINER	
CODE	MEASUREMENTS HEIGHT X WIDTH X LENGTH	APPROX. WEIGHT	MEASUREMENTS HEIGHT X WIDTH X LENGTH	CASE QTY.	WEIGHT	CASES	WEIGHT	PIECES	CASES	PIECES	CASES	PIECES	CASES	PIECES
1810-B	10 X 3.54 X 3.54 in	1.52 lb	6 X 5.5 X 10.24 in	2	3.40 lb	336	1174 lb	672	3360	6720	8064	16128	8736	17472
GENERAL SPECIFICATIONS														

SUNLIGHT RESISTANCE		ABRASION	RESISTANCE	WATER AB	SORPTION	STIFF	NESS	ELASTIC RECOVERY		
BLOCK	FIBER	BLOCK	FIBER	BLOCK	FIBER	BLOCK	FIBER	BLOCK	FIBER	
G	E	G	G	D	D	G	G	D	G	

THERMAL RESISTANCE*				CHEMICAL AND MOISTURE RESISTANCE											
DISTORTION		SOFTENING		MOISTURE DILUTED ACID		D ACID	CONCENTRATED ACID		DILUTED ALKALI		ALCOHOL AND VEGETABLE OILS		PETROLEUM DISTILLATES		
BLOCK	FIBER	BLOCK	FIBER	BLOCK	FIBER	BLOCK	FIBER	BLOCK	FIBER	BLOCK	FIBER	BLOCK	FIBER	BLOCK	FIBER
176 °F	127 °F	266 °F	185 °F	E	E	E	E	E	E	E	G	E	E	А	G

SUGGESTED APPLICATION:

Ideal for washing buses, trucks and trailer boxes since its two levels of fiber allow reaching high surfaces without losing the contact angle of the fiber.

G GOOD

CONTRAINDICATIONS:

These temperature was determined at constant exposure to heat / (1) Intermittent exposure does not affect it)

This brush should NOT be used in areas where high temperatures are handled.

E EXCELLENT

SUPPLEMENTARY PRODUCTS:

This brush can be used with any threaded handle in our line.



DNA DOES NOT APPLY



www.cepilloselcastor.com



A ADEQUATE (1)

D DEFICIENT

